



High Quality Price Ratio

[Flexible

Compact Design, suitable for limited application site

[Reliable]

Outstanding uptime, superior print quality on start-up

[Intelligent]

Fast replacement, modular design









Coding Tomorrow

www.leadtech.ltd LEAD TECH (ZHUHAI) ELECTRONIC CO., LTD.





Specifications


Printing Performance 1-4 Lines (7X5 matrix) 1-4 Lines (7X5 matrix) 1-4 Lines (5X5 matrix) 1-5 Lines (5X5 matrix) 1-1 Lines (7X5 matrix) 1-1 Lines (7X5 matrix) 1-1 Lines (7X5 matrix) 1-1 Lines (7X5 matrix) 1-	Model	LT800/LT810	LT800 Pro/LT810 Pro	LT880 HRS
Printing Performance 1-5 Lines (5X5 matrix)	Material	Precision coating/Stainless steel	Precision coating/Stainless steel	Precision coating
Twin-Line: 5X5, 7X5, 9x6, 12X8, 16X11 4 Lines: 5x5, 7x5 Printing Distance Character height: 1-15mm Printing distance: 2mm to 30mm Best: 10mm Operating System LT-Touch unique System, Multiple Languages Print Content English, Chinese, Arabic Numbers, serial number, Barcode, Shift, DM/QR Code, UPC A & E, EAN 8 & 13, Code 1 Code 125, GS1, UCC/EAN128, Code 39, automatic date/time/expiry date, special characters, etc. Extra Memory USB, RS485, Ethernet Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croati Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage In00+Messages In00+Messages Industrial Protection Super soft, length 3m, Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Ink (500ml) Make-up (750ml)		1-5 Lines (5X5 matrix)	1-5 Lines (5X5 matrix)	1-4 Lines (7X5 matrix) 1-5 Lines (5X5 matrix) Max. speed=430m/min@5x5
Printing distance: 2mm to 30mm Best: 10mm Operating System LT-Touch unique System, Multiple Languages Print Content English, Chinese, Arabic Numbers, serial number, Barcode, Shift, DM/QR Code, UPC A & E, EAN 8 & 13, Code 1 Code 125, GS1, UCC/EAN128, Code 39, automatic date/time/expiry date, special characters, etc. Extra Memory USB, RS485, Ethernet System Language Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croatic Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage In000+Messages IP55 Printhead Super soft, length 3m, Constant temperature, 60µm Printing Direction Ink (500ml) Make-up (750ml)	Font Matrix			
System English, Chinese, Arabic Numbers, serial number, Barcode, Shift, DM/QR Code, UPC A & E, EAN 8 & 13, Code 1 Code 125, GS1, UCC/EAN128, Code 39, automatic date/time/expiry date, special characters, etc. Extra Memory USB, RS485, Ethernet System Language Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croatic Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage Industrial Protection Printhead Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Ink (500ml) Make-up (750ml)				
Code 125, GS1, UCC/EAN128, Code 39, automatic date/time/expiry date, special characters, etc. Extra Memory USB, RS485, Ethernet Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croati Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage Industrial Protection Printhead Super soft, length 3m, Constant temperature, 60µm Constant temperature, 60µm Super soft, length 3m, Constant temperature, 60µm Constant temperature, 60µm Ink (500ml) Make-up (750ml)		LT-Touch unique System, Multiple Languages		
System Language Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croati Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage 1000+Messages IP55 Printhead Super soft, length 3m, Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Printing Direction 360°All-round printing Ink (500ml) Make-up (750ml)	Print Content	English, Chinese, Arabic Numbers, serial number, Barcode, Shift, DM/QR Code, UPC A & E, EAN 8 & 13, Code 128 A、B & C Code 125, GS1, UCC/EAN128, Code 39, automatic date/time/expiry date, special characters, etc.		
Language Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language Memory Storage 1000+Messages Industrial Protection IP55 Printhead Super soft, length 3m, Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Printing Direction 360°All-round printing Cartridge Volume Ink (500ml) Make-up (750ml)	Extra Memory	USB, RS485, Ethernet		
Storage 1000+Messages Industrial Protection IP55 Printhead Super soft, length 3m, Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Printing Direction 360°All-round printing Cartridge Volume Ink (500ml) Make-up (750ml)		Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croatian, Thai, Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language		
Protection IP55 Printhead Super soft, length 3m, Constant temperature, 60μm Constant temperature, 60μm Printing Direction 360°All-round printing Ink (500ml) Cartridge Volume Make-up (750ml)		1000+Messages		
Printhead Constant temperature, 60μm Constant temperature, 60μm Constant temperature Printing Direction 360°All-round printing Cartridge Volume Ink (500ml) Make-up (750ml)		IP55		
Direction 360°All-round printing Cartridge Volume Ink (500ml) Make-up (750ml)	Printhead	, , , ,	. , , ,	Super soft, length 3m, Constant temperature, 50μm
Volume Make-up (750ml)		360°All-round printing		
0.4500		, ,		
Femperature 0-45°C Humidity range 0-95% Relative Humidity, Non-condensing	Femperature Humidity range	0-45°C 0-95% Relative Humidity, Non-condensing		
Power AC100-240V, 50/60Hz,80VA	Power	AC100-240V, 50/60Hz,80VA		

^{*}LT800/LT810 is a standard model, LT800Pro/LT810Pro is a high-speed version with Network function, and LT880HRS is a high-speed, high-resolution, small font model (suitable for applications with high-precision fonts)

Dimensions









LEAD TECH (ZHUHAI) ELECTRONIC CO., LTD.

Tel: +86 756-7255629 Fax: +86 756-7255638 Web: www.leadtech.ltd

Add: Floor 3/4 , Building 1, No. 728, Jinhu Road, Sanzao Town, Jinwan District, Zhuhai City